



TOUGH ON TOUGHNESS



GUARDWEL PRODUCTS ARE RESISTANT TO

**OXY ACETYLENE
TORCH**

**FIRE &
IMPACT**

DRILL

CORROSION

**SOPHISTICATED
TOOLS**

**BURGLARY
ATTACKS**

ABOUT GUARDWEL

An ISO 9001, ISO 14001, ISO 45001 & CRISIL SME rated Company. Established in 1986, Guardwel Industries is a name synonymous for Physical Security Products. Our products are BIS Licensed with high level of Safety & Security. Promoted by Late Shri Anthony Tuscano, a veteran in Physical Security Products and an ace technocrat, his spirit has driven us to value our customer's expectations leading to their appreciation.

OUR PRODUCTS

All our products are designed as per the latest Indian Standards (IS), tested in-house & at BIS approved Test Houses, all our BIS Licensed products are affixed with BIS Label. We customize our products to suit the needs of customers, to provide them the desired solution. Our innovative development team continually upgrades our products to combat ever increasing security threats.




FIRE & BURGLAR RESISTANT SAFES

(Ref. Std IS 550) Class C (TL 30D * TL 10*5 - FR 30)

BIS LICENSED*


CM/L-750776



**STRONGER INNER
CASE BUILT**




**AUTOMATIC RE-
LOCKING SYSTEM**




**DETACHABLE SHELVES
LOCKABLE DRAWERS**



**MULTIPLE LOCK
OPTIONS**



**RESISTS ATTACKS
FOR 10 MINUTES
ON 5 SIDES**



**RESISTS ATTACKS
FOR 15 MINUTES
ON DOOR**

Technical Specifications:

Product	External Dimensions (mm)			Internal Dimensions (mm)			Volume (Litres)
	H	W	D	H	W	D	
FBR/470	680	555	567	480	355	295	50
FBR/580	790	640	657	590	440	385	100
FBR/850 (S)	1040	640	657	840	440	385	142
FBR / 850 (M)	1040	785	657	840	585	385	189
FBR/850 (L)	1040	785	720	840	585	448	220
FBR/1030	1245	785	720	1045	585	448	274
FBR/1340	1550	785	720	1350	585	448	354
FBR/1340 DD	1550	1090	720	1350	890	448	538
FBR/1860	2045	950	867	1845	750	595	823
FBR/1950 DD	2150	1290	867	1950	1090	595	1265
FBR/2050-DD	2250	1325	867	2050	1125	595	1372

Conversion factors: 25.4 mm = 1 inch 1 Kg = 2.2 Lbs Weight = 3 % Dimensions: +/-1%

TORCH & TOOL RESISTANT SAFES


(Ref. Std. IS 550) Class BB (TRTL 15*6)

BIS LICENSED*

CM/L-7507776



TORCH & TOOL
RESISTANCE




SUPERIOR QUALITY
BARRIERS



MULTIPLE LOCK
OPTIONS



BURGLARY ATTACK
RESISTANCE



RESISTS ATTACKS
FROM 6 SIDES
FOR 15 MINUTES

Technical Specifications:

Product	External Dimensions (mm)			Internal Dimensions (mm)			Volume (Litres)
	H	W	D	H	W	D	
TRTL BB Class 470	720	595	587	480	355	295	50
TRTL BB Class 580	830	680	677	590	440	385	100
TRTL BB Class 850 (S)	1080	680	677	840	440	385	142
TRTL BB Class 850 (M)	1080	825	677	840	585	385	189
TRTL BB Class 850 (L)	1080	825	740	840	585	448	220
TRTL BB Class 1030	1285	825	740	1045	585	448	274
TRTL BB Class 1340	1590	825	740	1350	585	448	354
TRTL BB Class 1340 DD	1590	1130	740	1350	890	448	538
TRTL BB Class 1860	2085	990	887	1845	750	595	823
TRTL BB Class 1950 DD	2190	1330	887	1950	1090	595	1265
TRTL BB Class 2050 DD	2290	1365	887	2050	1125	595	1372

Conversion factors: 25.4 mm = 1 inch 1 Kg = 2.2 Lbs Dimensions: +/-1%

NOTE COMMON TO ALL PRODUCTS : We reserve the right to alter any part of the specifications, as part of our continuous improvement without incurring any obligation.

* Only certain models approved by BIS.

TORCH & TOOL RESISTANT SAFES

((Ref. Std. IS 550) Class A (TRTL 30*6))

BIS LICENSED*

CM/L-750776



TORCH & TOOL
RESISTANCE




MULTIPLE LOCK
OPTIONS



SLEEK & STRONG
EXTERIOR BUILT



BURGLARY ATTACK
RESISTANCE



RESISTS ATTACKS
FROM 6 SIDES
FOR 30 MINUTES

- ✓ Built with special in-house made torch & tool resistant barrier of superior quality.
- ✓ Fitted with Guardwel dual control, 8 lever key locks with options of Mechanical Combination Lock, Time Lock and Electronic Keypad Lock are also available.

Technical Specifications:

Product	External Dimensions (mm)			Internal Dimensions (mm)			Volume (Litres)
	H	W	D	H	W	D	
TRTL A Class 470	720	595	607	480	355	293	50
TRTL A Class 580	830	680	697	590	440	383	100
TRTL A Class 850 (S)	1080	680	697	840	440	383	142
TRTL A Class 850 (M)	1080	825	697	840	585	383	189
TRTL A Class 850 (L)	1080	825	760	840	585	446	220
TRTL A Class 1030	1285	825	760	1045	585	446	274
TRTL A Class 1340	1590	825	760	1350	585	446	354
TRTL A Class 1340 DD	1590	1130	760	1350	890	446	538
TRTL A Class 1860	2085	990	907	1845	750	593	823
TRTL A Class 1950 DD	2190	1330	907	1950	1090	593	1265
TRTL A Class 2050 DD	2290	1365	907	2050	1125	593	1372

TORCH & TOOL RESISTANT SAFES

(Ref. Std. IS 550) Class AA (TRTL 60*6) & CLASS AAA (TRTL 90*6)

BIS LICENSED*

CM/L-7507776



Class AA (TRTL 60*6)



Class AAA (TRTL 90*6)



DUAL PROTECTION
AGAINST ATTACKS




STRONG
EXTERIOR BUILT



MULTIPLE LOCK
OPTIONS



SLEEK
AESTHETIC LOOK



RESISTS ATTACKS
FROM 6 SIDES
FOR 60 MINUTES

Technical Specifications:

Product	External Dimensions (mm)			Internal Dimensions (mm)			Volume (Litres)
	H	W	D	H	W	D	
TRTL AA Class 470	780	655	667	480	355	293	50
TRTL AA Class 580	890	740	757	590	440	383	100
TRTL AA Class 850 (S)	1140	740	757	840	440	383	142
TRTL AA Class 850 (M)	1140	885	757	840	585	446	189
TRTL AA Class 850 (L)	1140	885	820	840	585	446	220
TRTL AA Class 1030	1345	885	820	1045	585	446	274
TRTL AA Class 1340	1650	885	820	1350	585	446	354

GUARDWEL IoT Based BIOMETRIC ENABLED SMART Products



**A CLASS
SMART TRTL SAFES**




**B CLASS SMART
STRONG ROOM DOOR**



**AAA CLASS
SMART TRTL SAFES
(SMALL)**



**BURGLARY ATTACK
RESISTANCE**



**SLEEK & STRONG
AESTHETIC LOOK**



**DUAL CONTROL
8 LEVER KEY LOCKS**




DURESS ALERT



**DUAL
AUTHENTICATION**




**POWER FAIL AND
LOW BATTERY ALERTS**



**STORE LOGS FOR
SECURITY AUDIT**



**SMART FOG
SOLUTION (OPTIONAL)**



**CUSTOMIZED
SOLUTION**

Note:

1. Since the above products are available in various classes for technical specification kindly refer table of respective classes.
2. Customization available as per customer requirement and quantity.

GOLD LOAN SAFES

CM/L-7507776



Product Inner Height	Full Height No. of Minimum Trays	Full Height No. of Minimum Drawers
SAFE 470	3	2
SAFE 580	4	3
SAFE 850 (S)	5	5
SAFE 850 (M)	10	10
SAFE 850 (L)	10	10
SAFE 1030	12	12
SAFE 1340	16	16



HANGING HOOKS




GOLD LOAN TRAY




GOLD LOAN DRAWER




EASY STORAGE



ONLINE SERVER CONNECTIVITY



AVAILABLE IN VARIOUS SIZES



DRAWERS WITH KEY DETENTION MECHANISM (OPTIONAL)



Note:

1. Since the above products are available in various classes for technical specification kindly refer table of respective classes.
2. Customization available as per customer requirement and quantity.
3. Available in Various Classes

SAFE WITH SAFE DEPOSIT LOCKER


(Safe as per IS 550, SDLC Ref Std. IS 5244)



**FIRE & BURGLARY
ATTACK RESISTANCE
UPTO CLASS C**



**8 LEVER
DUAL CONTROL
HS LOCK**



**MULTIPLE LOCK
OPTIONS**



**TORCH & TOOL
RESISTANCE UPTO
CLASS AAA**



**AUTOMATIC RE-
LOCKING SYSTEM**



**IDEAL PROTECTION
IF STRONG ROOM
IS NOT FEASIBLE**

A standard or non-standard SDLC is housed inside a standard safe conforming to IS 550. Available in Classes C, BB, A, AA, AAA.

Technical Specifications:

Model	Lockers Combinations
	Number & SIZES
Safe 1340 with SDL-29	27A+2D1
Safe 1860 with SDL-36	24A+8C+4F
Safe 1860 with SDL-46	40A+4C+2F
Safe 1860 with SDL-56	56A
Safe 1950 DD with SDL-51	46B+2E+2H+1H1
Safe 1950 DD with SDL-75	66A+6C+3F
Safe 1950 DD with SDL-90	90A



Biometric Lock



Electronic Lock



Time Lock



Mechanical Combination Lock

Note: Besides the above any Standard SDLC 10,20,21,32,40,45,51,60,75 and 90 can be fitted inside a double door safe.

SAFE DEPOSIT LOCKER CABINET

(Ref. Std. IS 5244)

BIS LICENSED*

CM/L-7858001



**SMART LOCKER
SYSTEM**



**7 LEVER DUAL
CONTROL LOCK**



ROBUST BUILT




**SURFACE TREATMENT
PROCESS**



**CUSTOMIZED LOCKERS,
SPLIT INTO HORIZONTAL
OR VERTICAL PARTS**




**FIRE & BURGLARY
ATTACK RESISTANCE
UPTO CLASS C**



**LUMINA LOCKERS WITH
SLEEK LED LIGHTS**



**PADLOCKING
HASP**



**COLOURFUL
CLADDING**



**RENTERS
OWN LOCK**

Technical Specifications:

Model	As per BIS Type	Lockers			Internal Dimensions (mm)		
		Size		No.	H	W	D
SDL-90	Type 1A	A	A	90	125	180.5	503
SDL-75	Type 1	A	A	66	125	180.5	503
		2A	C	6	125	361.5	503
		4A	F	3	275	361	503
SDL-60	Type 4	B	B	60	159	216.5	503
SDL-51	Type 2A	B	B	46	159	216.5	503
		2B	E	2	159	434	503
		4B	H	2	328	434	503
		2B1	H1	1	328	216.5	503
SDL-45	Type 4	C	C	45	125	361.5	503
D		D	40	189	271	503	
SDL-32	Type 3	D	D	28	189	271	503
		2D	G	2	189	542.5	503
		4D	K	2	405	542.5	503
SDL-21	Type 4	F	F	21	275	361.5	503
G		G	20	189	542.5	503	
SDL-10		K1	K1	10	385	542.5	503

STRONG ROOM (VAULT) DOORS

(Ref. Std IS 11188) CLASS A (TRTL 60)

CLASS AA (TRTL120) CLASS AAA (TRTL 180)

BIS LICENSED*

CM/L-7956708



AAA CLASS SRD




A CLASS SRD


Our A, AA and AAA Class Vault doors are built rugged and have inherent features that provides perfect solution to combat the ever increasing attack techniques. Our SRDs are ideal for larger vaults or Currency chests.

Technical Specifications:

Specification	Ref	A CLASS	AA CLASS	AAA CLASS
		In mm	In mm	In mm
Dimension over Door Frame	A	1328 X 2245	1328 X 2245	1487 X 2310
Clear opening, door open at 180°	B	906 X 1995	906 X 1995	930 X 1995
Clear opening, door open at 90°	C	775	775	734
Wall opening	D	1100 X 2159	1100 X 2215	1200 X 2245
Projection of door open at 180°	E	305	330	422
Projection of door open at 90°	F	1115	1115	1231
Overall width of door & frame when door is open at 180°	G	2313	2353	2536
Min. Overall width of door & frame to give max clear opening	H	1565	1604	1934
Width over Grill Gate frame	J	1006	1006	1180
Projection of Grill Gate open at 180°	K	109	109	109
Projection of Grill Gate open at 90°	L	1039	1039	1087
Overall width of grill gate and frame when gate is open at 180°	M	2069	2069	2166
Centre line of door opening to the edge of the frame	N	664	664	743



BURGLARY ATTACK
RESISTANCE



FOLDABLE
FOOT-BRIDGE



MULTIPLE LOCK
OPTIONS



RETRO FITTING
OF TIME LOCK



TORCH & TOOL
RESISTANCE



DUAL PROTECTION - TWO HS
DUAL CONTROL KEY LOCKS WITH
NON-MAGNETIC KEYS IN DUPLICATE.
- REGULAR RIGHT HUNG OR
SPECIAL LEFT HUNG MODELS.

STRONG ROOM (VAULT) DOORS

(Ref. Std IS 11188) CLASS C (TRTL 15-FR 30) &
CLASS B (TRTL 30-FR 30)

BIS LICENSED*

CM/L-7956708



CLASS C
(TRTL 15-FR 30)



CLASS B
(TRTL 30-FR 30)

Technical Specifications:

Specification	Ref	C CLASS In mm	B CLASS In mm
Dimension over Door Frame	A	1211 X 2187	1323 X 2249
Clear opening, door open at 180°	B	911 X 1992	911 X 1992
Clear opening, door open at 90°	C	809	823
Wall opening	D	1096 X 2151	1096 X 2151
Projection of door open at 180°	E	236	236
Projection of door open at 90°	F	1077	1092
Overall width of door & frame when door is open at 180°	G	2187	2266
Min. Overall width of door & frame to give max clear opening	H	1521	1543
Width over Grill Gate frame	J	991	991
Projection of Grill Gate open at 180°	K	83	99
Projection of Grill Gate open at 90°	L	1002	1002
Overall width of grill gate and frame when gate is open at 180°	M	1982	1982
Centre line of door opening to the edge of the frame	N	606	662



**TORCH & TOOL
RESISTANCE**



**MULTIPLE LOCK
OPTIONS**




**FIRE & BURGLARY
ATTACK RESISTANCE
UPTO CLASS C**



**AUTOMATIC RE-
LOCKING SYSTEM
WHEN ATTACKED**



ROBUST BUILT



**LIGHT CONTROL SWITCH
ON THE MAIN DOOR**



**TWO HIGHLY SECURED DUAL
CONTROL KEY LOCKS (NON-
CORROSIVE & NON-MAGNETIC
KEYS) IN DUPLICATE**

GOLD SMITH DOOR (In Line with IS 7152)



A product specifically designed for Goldsmiths. The instances of robbery attempts with gas torch have been on the rise and have now spread from Banks to even Jewellery shops.




**TORCH & TOOL
RESISTANCE**



ROBUST BUILT



**TWO KEY LOCKS &
OPTIONS OF
TIME LOCK/BIOMETRIC
LOCK/MCL/ECL**




**CUSTOM
SIZED GSD**

Technical Specifications:

External (mm)	H-2035	W-1040
Clear Opening (mm)	H-1885	W-775

STRONG ROOM DOOR ACCESSORIES



AIR VENTILATOR WITH EXHAUST FAN & CAGE

Provides forced ventilation. Prevent Vaults from getting vacuum locked.



INSPECTION TROLLEY

Provides privacy for inspection of the valuables to the renters of lockers.



MOBILE LADDERS

Easy accessibility to operate upper section lockers of the SDLC.



LOW SETTEE

Easy accessibility to operate Lower section lockers of the SDLC.


TANG BARS




- ✓ Double combed, twisted Tang bars are a must for fortification of any Vault room or currency chest and offer the best resistance in case the Vaultwall comes under attack.
- ✓ Complete supervision service for laying the tang bars on request.
- ✓ Detailed specifications for all the above products are available on demand.

ADD ON PRODUCTS


CURRENCY BIN CABINETS



SOLUTION FOR
STORAGE OF
CURRENCY NOTES



AVAILABLE IN BC 2,
BC 4, BC 6, BC 8



CUSTOM SIZES (WITH/
WITHOUT PLINTH)

TECHNICAL SPECIFICATIONS:

Model	External Dimensions (mm)			Internal Dimensions (mm)			No. of Bins
	H	W	D	H	W	D	
BC 2 with Plinth	587	1830	760	480	913	692	2
BC 2 without Plinth	512	1830	760	480	913	692	2
BC 4 with Plinth	1068	1830	760	480	913	692	4
BC 4 without Plinth	993	1830	760	480	913	692	4
BC 6 with Plinth	1549	1830	760	480	913	692	6
BC 8 with Plinth	2030	1830	760	480	913	692	8
BC 10 with Plinth	2512	1830	760	480	913	692	10

FIRE RESISTING FILING CABINET

(Ref.Std IS 14561) (FR 120 & FR 60)

BIS LICENSED

CM/L-3907570

RIGOROUS TESTS PASSED AT BIS ACCREDITED TEST HOUSES

- ✓ Fire endurance test at 1045°C & 945°C for 120 minutes & 60 minutes
- ✓ Fire & Impact test for 45 minutes & 30 minutes respectively

RIGOROUS IN-HOUSE TESTING


- ✓ 5000 cycles test for strength of cradle strips and drawer suspension with 30kg load
- ✓ Cross hatch test for paint adhesion
- ✓ Salt spray test for corrosion resistance




Technical Specifications:

Model	External Dimensions (mm)		
	H	W	D
FRFC 4 Drawer	1572	541	804
FRFC 3 Drawer	1210	541	804
FRFC 2 Drawer	845	541	804
FRFC 1 Drawer	483	541	804
Clear inside dimensions of drawer	289	385	650
Volume per drawer 72 Litres			


For 1 Drawer FRFC, minimum quantities = 5 Nos.




A UNIQUELY
DESIGNED HANDLES




TIMELESS FIRE
RESISTING
COMPOUND




REINFORCED
CORNERS




HEAVILY INSULATED
5-SIDE ENCLOSURE



NINE TANK
ANTI-CORROSION
TREATMENT



AVAILABLE IN 4, 3, 2
& 1-DRAWER MODELS




PREVENTS HOT
GASES & FLAMES




LIGHTER
WEIGHT




BEST RESISTANCE
TO FIRE



REDUCED LOAD
ON THE FLOOR



EACH DRAWER INDIVIDUALLY
INSULATED TO WITHSTAND
TEMPERATURES UP TO 1000°C



DOUBLE EXTENSION
TELESCOPIC SLIDES WITH
HEAVY DUTY BALL BEARINGS

FIRE RESISTANT RECORD PROTECTION CABINET

(Ref. Std. IS 14203)

BIS LICENSED

CM/L-7700067016



FRRC

with Drawers

- ✓ Fire endurance test at 1045°C for 120minutes FR 120 & 945°C for FR 60.
- ✓ Fire and Impact test for 45 minutes for FR 120 & 30 mins for FR 60.
- ✓ Provides ultimate safety for valuable records and storage media. 6 lever dual control key locking mechanism. Available with the options of : Drawers fitted on extendable trolleys suitable for storage of documents /certificates.
- ✓ Built in locker unit for additional confidentiality.



FRRC

with Shelves

Technical Specifications:

Model	External Dimensions (mm)			Internal Dimensions (mm)		
	H	W	D	H	W	D
FRRC with 4 shelves	1830	820	750	1600	660	586
	(72")	(32")	(29.5")	(63")	(26")	(22.8")

Important: Please allow 50mm projection for door furniture on external depth measurement.

COMPUTER DATA CABINET



Guardwel CDC, protect data on computer tapes, magnetic media from heat, dust & moisture. Double cabinet construction with an insulated cabinet inside a FRRC with 4 shelves, but optional internals can be customized to match customer preferences.

Technical Specifications:

Model	External Dimensions (mm)			Internal Dimensions (mm)		
	H	W	D	H	W	D
CDC	1830	820	750	1475	540	380
	(72")	(32")	(29 1/2")	(58")	(21 1/4")	(15 1/8")

Important: Please allow 50mm projection for door furniture on external depth measurement.

FIRE RESISTANT COMPACTORS

**1 BAY DFDB
COMPACTOR**




**2 BAY DFDB
COMPACTOR ON TROLLEY**



**3 BAY DFDB
COMPACTOR ON TROLLEY**



In metros, where floor space is the most preciously valued commodity, our fire resistant compactors are ideal solution for safe storage of records in fire risk zone. Fire Resistant Record Protection Cabinet, modified and installed in a back-to-back construction on a rail movement system, are sturdy enough to withstand heavy usage, offers smooth handling and ease of accessibility. We customize Fire Resistant Compactors to match and suit the space available in an office.



**MAXIMIZES SPACE
UTILISATION**



**FIRE RESISTANT
BARRIER**



**EASY IDENTIFICATION
& ACCESSIBILITY**




**STRONG
BUILT**



**HIGH SECURITY
LOCKING**



EASY OPERATION



CUSTOMIZATION


PRODUCT	EXTERNAL DIMENSION (mm)		
	H	W	D
SINGLE FACE FRRC	1730	790	750
DOUBLE FACE COMMON BACK FRRC (DFCB)	1730	790	1003

REGENT SAFES



Technical Specifications:


Technical Specification	Regent 22	Regent 27
Outside: Height (H)	560	685
Width (W)	460	535
Depth (D)	460	510
w/o Handle		
Inside: Height (H)	554(354+200 locker)	679(479+200 locker)
Width (W)	454	529
Depth (D)	385	435
Sheet thickness	3mm	3mm
Internal Cubic Capacity (liters)	97	155
Door Swing	375	450
Guardwel Locks	one 6-lever dual control lock	one 6-lever dual control lock
Lockers	one	one
Shelves	one (removable)	one (removable)
Net weight Kgs (approx.)	55	75
Gross weight Kgs (approx.)	60	80




**FULLY WELDED
MULTI-BEND BODY**




**GREATER
SECURITY**




**A HEAVY PLATE
DOOR HINGED ON
STRONG PIVOTS**




**ADEQUATE RESISTANCE
TO THE IMPACT
OF HAMMER**



**THE REAR EDGE OF
THE DOOR ACTS LIKE
A CONTINUOUS
VERTICAL BOLT**




**A LOCKER WITH A
FLAP DOOR & LOCK TO
FACILITATE ADDITIONAL
SECURITY**



**DUAL CONTROL
6-LEVER LOCK
OPERATED BY 2 KEYS**




**AVAILABLE WITH A
COIN SLOT MEASURING
15X100 MM & BAFFLE
TRAY (OPTIONAL)**



**3-WHEEL NUMERICAL
COMBINATION
LOCK (AT REQUEST)**



DEALERS NETWORK ACROSS INDIA



Our dealers are spread all across the country, prepared to serve with our product and services. These dealers are equipped to fulfil all needs for any security products in any part of the country.